



TECHNICAL DATA

Order no.	82995.2
Certified to	EN 14055
matching for	Floorstanding WC pan order no. 82595.2, 82595.1 / Charge 000, 82596.2 / Charge 000
Specification	Flushing mechanism Dual-Flush With water condensation insulation: Charge 872 – 5/3-l (6/3-l-flush, 4,5/3-l-flush) Without water condensation insulation: Charge 876 – 5/3-l (6/3-l-flush, 4,5/3-l-flush)
Water inlet	side left, side right, 3/8" brass
Weight	10,0 kg
Mounting acc. incl.	Fastening kit
Mounting acc. excl.	Angle valve for water inlet Water inlet hose
Colours	see colour table

SPECIFICATION TEXT

Cistern LAUFEN PRO, sanitary ceramic
EN 14055
dimensions 375 x 160 x 395 mm
Dual-Flush 5/3-l (6/3-l-flush, 4,5/3-l-flush)
water inlet side left, side right, 3/8" brass
matching floorstanding WC pan, order no. 82595.1/option 000,
82595.2/option 000, 82596.2 / option 000
Special feature: with or without water condensation insulation
Further options: Surface refinement LCC (only white)
Order no. 82995.2

TECHNICAL DRAWINGS / S 1 : 20

