



**TECHNICAL DATA**

Order no.	82695.2	Weight	12,2 kg
Certified to	EN 14055	Mounting acc. incl.	Fastening kit
matching for	Floorstanding WC pan order no. 82495.5 / Charge 000/204 82495.6, 82495.7, 82495.8 / Charge 000/204, 82495.9	Mounting acc. excl.	Angle valve for water inlet Water inlet hose
Specification	Flushing mechanism Dual-Flush 5/3-l (6/3-l-flush, 4,5/3-l-flush) Charge 872 – with water condensation insulation Charge 876 – without water condensation insulation Charge 893 – without water condensation insulation (project version)	Colours	see colour table
Water inlet	side left, side right, 3/8" brass	<b>SPECIFICATION TEXT</b> Cistern LAUFEN PRO, sanitary ceramic EN 14055 dimensions 380 x 175 x 360 mm Dual-Flush 5/3-l (6/3-l-flush, 4,5/3-l-flush) water inlet side left, side right, 3/8" brass matching floorstanding WC pan, order no. 82495.5 option 000/204, 82495.6, 82495.7, 82495.8 option 000/204, 82495.9 Special feature: with or without water condensation insulation Further options: Surface refinement LCC (only white) Order no. 82695.2	

**TECHNICAL DRAWINGS / S 1 : 20**

